

PAT-NO: JP410269345A

DOCUMENT-IDENTIFIER: JP 10269345 A

TITLE: TWO-DIMENSIONAL INFORMATION PROCESSOR

PUBN-DATE: October 9, 1998

INVENTOR-INFORMATION:

NAME

IWATA, ATSUSHI

NAGATA, MAKOTO

ASSIGNEE-INFORMATION:

NAME

HIROSHIMA UNIV

COUNTRY

N/A

APPL-NO: JP09078025

APPL-DATE: March 28, 1997

INT-CL (IPC): G06T001/00, G06T009/20

ABSTRACT:

PROBLEM TO BE SOLVED: To execute a high grade processing by processing information between respective cells on the two-dimensional sensor surface of a sensor.

SOLUTION: A two-dimensional picture sensor is constituted of unit cell circuits 1, an address ramp waveform generating circuit 2, address lines 3, a bus line 4, a pulse width/electric charge detecting circuit 5 and a shutter 19. The unit cell circuits 1 are arranged in a two-dimensional matrix-shape. The respective unit cell circuits 1 are connected to the plural address lines 3 which are extended from the address ramp waveform generating circuit 2 to a string direction. When two-dimensional optical information from an outside is inputted, the whole matrix surface is exposed to light. Unit cells are made to store two-dimensional information which is optically or electrically written and a ramp waveform voltage is selectively supplied to the prescribed unit cell so that a pulse width modulation(PWM) signal is generated, which rises at the increase start time of the ramp waveform voltage and falls at a time when the voltage corresponding to stored information quantity coincides with the supplied ramp waveform voltage.

COPYRIGHT: (C)1998,JPO